

IN THE CLAIMS

Please amend the claims as follows:

A' Claim 1 (Currently Amended): Scanning optics comprising:  
first optics for coupling a light beam issuing from a light source;  
second optics for condensing the light beam output from said first optics substantially  
in a form of a line ~~elongate~~ elongated in a main scanning direction;  
a deflector including reflection faces, which adjoin a position where the light beam is  
condensed in the form of a line, for deflecting said light beam with said reflection faces; and  
third optics for condensing the light beam deflected by said deflector toward a surface  
to be scanned to thereby form a beam spot on said surface for optically scanning said surface;  
wherein said third optics includes at least one focusing element formed of resin;  
said second optics includes at least one focusing element formed of resin and at least  
one focusing element formed of glass,  
at least one surface of said second optics comprises a non-arcuate auxiliary surface  
non-arcuate in a section in a subscanning direction, and  
among said focusing elements of said second optics, a focusing element ~~through~~ on  
which the light beam output from said first optics is transmitted with a maximum diameter in  
the subscanning direction comprises said at least one non-arcuate auxiliary surface.

Claim 2 (Currently Amended): The scanning optics as claimed in claim 1, wherein  
said third optics includes said at least one ~~arcuate~~ non-arcuate auxiliary surface.

Claim 3 (Original): The scanning optics as claimed in claim 1, wherein among said  
focusing elements of said second optics, a surface of the focusing element through which the

light beam output from said first optics is transmitted with the maximum diameter in the subscanning direction comprises said at least one non-arcuate auxiliary surface.

A' Claim 4 (Currently Amended): The scanning optics as claimed in claim 3, wherein the at least one focusing element formed of resin of said second optics comprises two lenses formed of resin and the at least focusing element formed of glass of said second optics comprises a single lens formed of glass,

said two lenses formed of resin adjoin said first optics and have negative power in the subscanning direction,

said single lens formed of glass adjoins said deflector and has positive power in the subscanning direction, and

at least one of said two lenses formed of resin has power in the main scanning direction opposite to power of said focusing element of said third optics formed of resin in the main scanning direction.

Claim 5 (Original): The scanning optics as claimed in claim 4, wherein one of said two lenses formed of resin has a concave, spherical input surface and a concave, cylindrical output surface and adjoins said first optics,

the other of said two lenses comprises a cylindrical lens having negative power in the subscanning direction, and

said single lens formed of glass comprises a toroidal lens having positive power in the main and subscanning directions and is positioned closer to said deflector than said cylindrical lens and has a non-arcuate auxiliary input surface.

Claim 6 (Currently Amended): The scanning optics as claimed in claim 5, wherein said third optics includes ~~said~~ at least one non-arcuate auxiliary surface.

Claim 7 (Currently Amended): The scanning optics as claimed in claim 1, wherein the at least one focusing element formed of resin of said second optics comprises two lenses formed of resin and the at least focusing element formed of glass of said second optics comprises a single lens formed of glass,

A' said two lenses formed of resin adjoin said first optics and have negative power in the subscanning direction,

said single lens formed of glass adjoins said deflector and has positive power in the subscanning direction, and

at least one of said two lenses formed of resin has power in the main scanning direction opposite to power of said focusing element of said third optics formed of resin in the main scanning direction.

Claim 8 (Original): The scanning optics as claimed in claim 7, wherein one of said two lenses formed of resin has a concave, spherical input surface and a concave, cylindrical output surface and adjoins said first optics,

the other of said two lenses comprises a cylindrical lens having negative power in the subscanning direction, and

said single lens formed of glass comprises a toroidal lens having positive power in the main and subscanning directions and is positioned closer to said deflector than said cylindrical lens and has a non-arcuate auxiliary input surface.

Claim 9 (Currently Amended): The scanning optics as claimed in claim 8, wherein said third optics includes ~~said~~ at least one non-arcuate auxiliary surface.

Claims 10-18 (Canceled).

A<sup>1</sup>  
Claim 19 (Currently Amended): In an optical scanning device including scanning optics that couples a light beam issuing from a light source with first optics, condenses a coupled light beam with second optics substantially in a form of a line ~~elongate~~ elongated in a main scanning direction, deflects a condensed light beam with a deflector including reflection faces, which adjoin a position where said light beam is condensed in the form of a line, and then condenses a deflected light beam toward a surface to be scanned with third optics to thereby form a beam spot on said surface for thereby optically scanning said surface, said third optics includes at least one focusing element formed of resin,

said second optics includes at least one focusing element formed of resin and at least one focusing element formed of glass,

at least one surface of said second optics comprises a non-arcuate auxiliary surface non-arcuate in a section in a subscanning direction, and

among said focusing elements of said second optics, a focusing element ~~through~~ on which the light source output from said first optics is transmitted with a maximum diameter in the subscanning direction comprises said at least one non-arcuate auxiliary surface.

Claim 20 (Currently Amended): In an optical scanning device including scanning optics that couples a light beam issuing from a light source with first optics, condenses a coupled light beam with second optics substantially in a form of a line ~~elongate~~ elongated in a main scanning direction, deflects a condensed light beam with a deflector including reflection

faces, which adjoin a position where said light beam is condensed in the form of a line, and then condenses a deflected light beam toward a surface to be scanned with third optics to thereby form a beam spot on said surface for thereby optically scanning said surface, said third optics includes at least one focusing element formed of resin,

said second optics includes at least one focusing element formed of resin and at least one focusing element formed of glass,

at least one surface of said second optics comprises a non-arcuate auxiliary surface non-arcuate in a section in a subscanning direction, and

A' among said focusing elements of said second optics, a focusing element formed of resin ~~through~~ on which the light beam output from said first optics is transmitted with a maximum diameter in the subscanning direction comprises said at least one non-arcuate auxiliary surface.

Claim 21 (Currently Amended): In an image forming apparatus including an optical scanning device for scanning an image carrier, said optical scanning device comprising scanning optics that couples a light beam issuing from a light source with first optics, condenses a coupled light beam with second optics substantially in a form of a line ~~elongate~~ elongated in a main scanning direction, deflects a condensed light beam with a deflector including reflection faces, which adjoin a position where said light beam is condensed in the form of a line, and then condenses a deflected light beam toward a surface of said image carrier with third optics to thereby form a beam spot on said surface for thereby optically scanning said surface, said third optics includes at least one focusing element formed of resin, said second optics includes at least one focusing element formed of resin and at least one focusing element formed of glass,

at least one surface of said second optics comprises a non-arcuate auxiliary surface non-arcuate in a section in a subscanning direction, and

among said focusing elements of said second optics, a focusing element ~~through~~ on which the light beam output from said first optics is transmitted with a maximum diameter in the subscanning direction comprises said at least one non-arcuate auxiliary surface.

Claim 22 (Original): The apparatus as claimed in claim 21, wherein said image carrier comprises a photoconductive element, and said optical scanning device forms a latent image on said photoconductive element.

A  
Claim 23 (Currently Amended): In an image forming apparatus including an optical scanning device for scanning an image carrier, said optical scanning device comprising scanning optics that couples a light beam issuing from a light source with first optics, condenses a coupled light beam with second optics substantially in a form of a line ~~elongate~~ elongated in a main scanning direction, deflects a condensed light beam with a deflector including reflection faces, which adjoin a position where said light beam is condensed in the form of a line, and then condenses a deflected light beam toward a surface of said image carrier with third optics to thereby form a beam spot on said surface for thereby optically scanning said surface, said third optics includes at least one focusing element formed of resin[[:]],

said second optics includes at least one focusing element formed of resin and at least one focusing element formed of glass,

at least one surface of said second optics comprises a non-arcuate auxiliary surface non-arcuate in a section in a subscanning direction, and

among said focusing elements of said second optics, a focusing element formed of resin ~~through~~ on which the light beam output from said first optics is transmitted with a maximum diameter in the subscanning direction comprises said at least one non-arcuate auxiliary surface.

A  
Claim 24 (Original): The apparatus as claimed in claim 23, wherein said image carrier comprises a photoconductive element, and said optical scanning device forms a latent image on said photoconductive element.

---